Please provide the following information, and submit to the NOAA DM Plan Repository.

Reference to Master DM Plan (if applicable)

As stated in Section IV, Requirement 1.3, DM Plans may be hierarchical. If this DM Plan inherits provisions from a higher-level DM Plan already submitted to the Repository, then this more-specific Plan only needs to provide information that differs from what was provided in the Master DM Plan.

URL of higher-level DM Plan (if any) as submitted to DM Plan Repository:

1. General Description of Data to be Managed

1.1. Name of the Data, data collection Project, or data-producing Program:

2018 OLC Lidar: Santiam, OR

1.2. Summary description of the data:

This GIS dataset contains points, polygons, and raster grids depicting lidar-derived elevation data for the Oregon Lidar Consortium (OLC) Santiam 2018 area of interest (AOI). The AOI encompasses 106,585 acres within area of interest (AOI), and 110,378 acres within the buffered area of interest (BAOI). All data are in Polk and Marion Counties, Oregon. The nominal pulse density is eight pulses per square meter. The digital elevation model (DEM) and digital surface model (DSM) raster grid cell size is 3 feet. The intensity raster grid cell size is 1.5 feet. The native projection is Oregon Statewide Lambert, Lambert Conformal Conic, units are in international feet. The native horizontal datum is NAD83(2011) and the native vertical datum is NAVD88 (Geoid 12B). Quantum Spatial Inc. collected the lidar and created this dataset for the Oregon Department of Geology and Mineral Industries (DOGAMI).

The NOAA Office for Coastal Management received the point data and processed it to the Data Access Viewer (DAV) and http. The data were converted to geographic coordinates and ellipsoidal heights for DAV, and geographic coordinates and orthometric heights using NAVD88 for http.

1.3. Is this a one-time data collection, or an ongoing series of measurements? One-time data collection

1.4. Actual or planned temporal coverage of the data:

2018-11-18 to 2018-11-20

1.5. Actual or planned geographic coverage of the data:

W: -123.131443, E: -122.705748, N: 45.044279, S: 44.709907

1.6. Type(s) of data:

(e.g., digital numeric data, imagery, photographs, video, audio, database, tabular data, etc.)
Model (digital)

1.7. Data collection method(s):

(e.g., satellite, airplane, unmanned aerial system, radar, weather station, moored buoy, research vessel, autonomous underwater vehicle, animal tagging, manual surveys, enforcement activities, numerical model, etc.)

1.8. If data are from a NOAA Observing System of Record, indicate name of system:

1.8.1. If data are from another observing system, please specify:

2. Point of Contact for this Data Management Plan (author or maintainer)

2.1. Name:

NOAA Office for Coastal Management (NOAA/OCM)

2.2. Title:

Metadata Contact

2.3. Affiliation or facility:

NOAA Office for Coastal Management (NOAA/OCM)

2.4. E-mail address:

coastal.info@noaa.gov

2.5. Phone number:

(843) 740-1202

3. Responsible Party for Data Management

Program Managers, or their designee, shall be responsible for assuring the proper management of the data produced by their Program. Please indicate the responsible party below.

3.1. Name:

3.2. Title:

Data Steward

4. Resources

Programs must identify resources within their own budget for managing the data they produce.

4.1. Have resources for management of these data been identified?

Yes

4.2. Approximate percentage of the budget for these data devoted to data management (specify percentage or "unknown"):

Unknown

5. Data Lineage and Quality

NOAA has issued Information Quality Guidelines for ensuring and maximizing the quality,

objectivity, utility, and integrity of information which it disseminates.

5.1. Processing workflow of the data from collection or acquisition to making it publicly accessible

(describe or provide URL of description):

Process Steps:

- 2018-11-21 00:00:00 - 1. TRAJECTORY: Aircraft trajectory (position and attitude) were calculated based on on-board GPS and IMU data with post-processing refinement through coincident static GPS collection. 2. POST-PROCESSING: Laser point return coordinates (x,y,z) were computed using sensor-specific post processing software, combining LiDAR return range and intensity information with aircraft trajectory information. 3. INITIAL QAQC: The post-processed LiDAR files were assembled into flight lines and reviewed for gaps and consistency, as well as systematic noise. 4. CALIBRATION: Custom algorithms evaluated individual swaths for misalignments based on IMU configuration as well as aircraft attitude variability. Offsets were resolved through surface and linear matching algorithms that minimize variability in elevation and slope. Descriptive statistics, thresholds, and specifications providing transparency for data calibration are discussed in the accompanying Data Report. 5. GROUND MODELING: Ground classified point cloud was generated through proprietary data processing tools, with settings and thresholds appropriate to landscape and vegetation condition. 6. ARTIFACT FILTRATION: Noise and processing artifacts were filtered using post-processing software and proprietary quality control methods. 7. ACCURACY ASSESSMENT: Vertical accuracy for the LiDAR dataset was assessed against reserved Quality Assurance Points (OAPs) distributed throughout the study area and not used during calibration processes. See the accompanying Data Report for methodology, descriptive statistics, and relevant standards and reporting language. 8. DATA PRODUCT: LiDAR points classified as 'ground' were output as a digital elevation model (DEM). 9. Hydro Flattening Breakline Processing: Class 2 LiDAR was used to create a bare earth surface model. E-Cognition utilized rasters created within Bentley Microstation to auto-generate breaklines of inland streams and rivers with a 100 foot nominal width and Inland Ponds of 2 acres or greater surface area. Breaklines for Lakes with surface area greater than 2 acres were generated using heads-up digitization. Elevation values were assigned to all Inland Ponds and Lakes within ESRI ArcMap; Inland Pond and Lake Islands, Inland Stream and River Islands were assigned elevation values from within ESRI ArcMap. All ground (ASPRS Class 2) LiDAR data inside of the collected inland breaklines were then classified to water (ASPRS Class 9) using TerraScan macro functionality. A buffer of 2.1 meter was also used around each hydro-flattened stream. These points were moved from ground (ASPRS Class 2) to Ignored Ground (ASPRS Class 10). The breakline files were then translated to ESRI File-Geodatabase format using ESRI conversion tools. (Citation: Raw Lidar)

- 2019-10-11 00:00:00 - Data was obtained by NOAA Office for Coastal Management from DOGAMI. Data were in Oregon Lambert NAD83(2011) international feet with NAVD88(Geoid12B) international feet vertically. Data were converted to geographic

coordinates in ellipsoid heights (meters) using the general cartographic transform package subroutines and reversing the application of GEOID12B.

5.1.1. If data at different stages of the workflow, or products derived from these data, are subject to a separate data management plan, provide reference to other plan:

5.2. Quality control procedures employed (describe or provide URL of description):

6. Data Documentation

The EDMC Data Documentation Procedural Directive requires that NOAA data be well documented, specifies the use of ISO 19115 and related standards for documentation of new data, and provides links to resources and tools for metadata creation and validation.

6.1. Does metadata comply with EDMC Data Documentation directive?

No

6.1.1. If metadata are non-existent or non-compliant, please explain:

Missing/invalid information:

- 1.7. Data collection method(s)
- 3.1. Responsible Party for Data Management
- 5.2. Quality control procedures employed
- 7.1.1. If data are not available or has limitations, has a Waiver been filed?
- 7.4. Approximate delay between data collection and dissemination
- 8.3. Approximate delay between data collection and submission to an archive facility

6.2. Name of organization or facility providing metadata hosting:

NMFS Office of Science and Technology

6.2.1. If service is needed for metadata hosting, please indicate:

6.3. URL of metadata folder or data catalog, if known:

https://www.fisheries.noaa.gov/inport/item/57943

6.4. Process for producing and maintaining metadata

(describe or provide URL of description):

Metadata produced and maintained in accordance with the NOAA Data Documentation Procedural Directive: https://nosc.noaa.gov/EDMC/DAARWG/docs/EDMC_PD-Data Documentation v1.pdf

7. Data Access

NAO 212-15 states that access to environmental data may only be restricted when distribution is explicitly limited by law, regulation, policy (such as those applicable to personally identifiable information or protected critical infrastructure information or proprietary trade information) or by

security requirements. The EDMC Data Access Procedural Directive contains specific guidance, recommends the use of open-standard, interoperable, non-proprietary web services, provides information about resources and tools to enable data access, and includes a Waiver to be submitted to justify any approach other than full, unrestricted public access.

7.1. Do these data comply with the Data Access directive?

Yes

- 7.1.1. If the data are not to be made available to the public at all, or with limitations, has a Waiver (Appendix A of Data Access directive) been filed?
- 7.1.2. If there are limitations to public data access, describe how data are protected from unauthorized access or disclosure:

7.2. Name of organization of facility providing data access:

NOAA Office for Coastal Management (NOAA/OCM)

7.2.1. If data hosting service is needed, please indicate:

7.2.2. URL of data access service, if known:

https://coast.noaa.gov/dataviewer/#/lidar/search/where:ID=8895 https://coast.noaa.gov/htdata/lidar3_z/geoid18/data/8895

7.3. Data access methods or services offered:

Data is available online for custom downloads

- 7.4. Approximate delay between data collection and dissemination:
 - 7.4.1. If delay is longer than latency of automated processing, indicate under what authority data access is delayed:

8. Data Preservation and Protection

The NOAA Procedure for Scientific Records Appraisal and Archive Approval describes how to identify, appraise and decide what scientific records are to be preserved in a NOAA archive.

8.1. Actual or planned long-term data archive location:

(Specify NCEI-MD, NCEI-CO, NCEI-NC, NCEI-MS, World Data Center (WDC) facility, Other, To Be Determined, Unable to Archive, or No Archiving Intended) NCEI_CO

- 8.1.1. If World Data Center or Other, specify:
- 8.1.2. If To Be Determined, Unable to Archive or No Archiving Intended, explain:

8.2. Data storage facility prior to being sent to an archive facility (if any):

Office for Coastal Management - Charleston, SC

8.3. Approximate delay between data collection and submission to an archive facility:

8.4. How will the data be protected from accidental or malicious modification or deletion prior to receipt by the archive?

Discuss data back-up, disaster recovery/contingency planning, and off-site data storage relevant to the data collection

Data is backed up to tape and to cloud storage.

9. Additional Line Office or Staff Office Questions

Line and Staff Offices may extend this template by inserting additional questions in this section.